Document of Performance
According to Regulation (EU) 305/2011

Aduro Hybrid Series H1, H2, H3 Lux, H4 Lux Roomheater burning solid fuel without hot water supply. EN 16510-2-1:2022/A2:2004/AC:2007 Residential space heating appliance fired by wood pellets without hot water supply. EN 16510-2-6:2022	DoP No: H1 0001
Aduro AS, Hasselager Allé 13D, DK-8260 Viby J. Adurofire.com / info@aduro.dk	
System 3 of assessment and verification of constancy of performance of the construction product: Internal quality security system in combination with external production control.	
Teknologisk Institut, Kongsvang 29, DK-8000 Aarhus, notified body number: 1235. performed the determination of the product type on the basis of type testing under system 3 and issued test report: 300-ELAB-2309-EN, 300-ELAB-2250-EN-WL	

Declared performance

Harmonized technical specification	**EN 16510-2-1:2022/A2:2004/AC:2007**
	EN 16510-2-6:2022
Essential characteristics	**Performance**
Fire safety	
Reaction to fire	A1
Distance to combustible materials	Minimum distances, in mm rear = 75 sides: - with side glass = 700 - without side glass = 400 - Corner (only without side glass) = 100 front = 1000
Risk of burning fuel falling out	Pass
Emission of combustion products Wood	CO [0.1 %]
Emission of combustion products Pellets Nominal Heat	CO [0.02 %]
Emission of combustion products Pellets Reduced Heat	CO [0.02 %]
Surface temperature	Pass
Electrical safety	Pass
Cleanability	Pass
Maximum water operating pressure	NPD
Flue gas temperature at nominal heat output Wood	T [228°C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Nominal heat output Wood Room heating output Water heating output	7,0 kW 7,0 kW "" kW
Nominal heat output Pellets Room heating output Water heating output	6,8 kW 6,8 kW "" kW
Energy efficiency Wood	η [81 %]
Energy efficiency Pellets	η [87 % by Nominal output] η [87 % by Reduced output]

Signed for and on behalf of the manufacturer by:

Christian Skovbo, CEO, Aduro AS
Viby J, 21.08.2025