

Document of Performance According to Regulation (EU) 305/2011

Aduro Hybrid Series H5

DoP No: H5 0001

Roomheater burning solid fuel without hot water supply.

EN 16510-2-1:2022/A2:2004/AC:2007

Residential space heating appliance fired by wood pellets without hot water supply.

EN 16510-2-6:2022

Aduro AS, Hasselager Allé 13D, DK-8260 Viby J. Adurofire.com / info@aduro.dk

System 3 of assessment and verification of constancy of performance of the construction product: Internal quality security system in combination with external production control.

Teknologisk Institut, Kongsvang 29, DK-8000 Aarhus, notified body number: 1235. performed the determination of the product type on the basis of type testing under system 3 and <u>issued test report:</u> 300-ELAB-2388-EN

Declared performance

Harmonized technical specification	EN 16510-2-1:2022/A2:2004/AC:2007
	EN 16510-2-6:2022
Essential characteristics	Performance
Fire safety	
Reaction to fire	A1
Distance to combustible materials	Minimum distances, in mm
Distance is for installation with 1000 mm isolated pipe	rear = 50 from air intake, 70 mm from the back of the stove
	sides = 375
	front = 1000
Risk of burning fuel falling out	Pass
Emission of combustion products Wood	CO[0.1 %]
Emission of combustion products Pellets Nominal Heat	CO[0.02 %]
Emission of combustion products Pellets Reduced	CO[0.02 %]
Heat	
Surface temperature	Pass
Electrical safety	Pass
Cleanability	Pass
Maximum water operating pressure	NPD
Flue gas temperature at nominal heat output Wood	T [210°C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Nominal heat output Wood	7,0 kW
Room heating output	7,0 kW
Water heating output	*" kW
Nominal heat output Pellets	6,8 kW
Room heating output	6,8 kW
Water heating output	"" kW
Energy efficiency Wood	η [83 %]
Energy efficiency Pellets	η [87 % by Nominal output] η [87 % by Reduced output]

Signed for and on behalf of the manufacturer by:

Christian Skovbo, CEO, Aduro AS

Viby J, 21.08.2025

Chel SIL